

1U DC-MHS Server with Dual Intel® Xeon® 6 Processors

S11

EnGenius S11 is a 1U compact modular server built on the Intel® Xeon® 6 platform and OCP DC-MHS standard. It supports up to 12x NVMe drives and 2x PCIe Gen5 slots, making it ideal for virtualization, AI workloading, and private cloud deployments. The CPU offers P-core/E-core architecture, efficient airflow design, and centralized EDCC management. S11 delivers outstanding compute density and flexibility for modern data centers.



Performance

Dense 1U Compute

Dual Intel® Xeon® 6 with P-core/E-core architecture in a compact 1U footprint.

Storage

High-Density NVMe

Up to 12x 2.5" U.2 NVMe PCIe Gen5 hot-swap bays with Intel VROC support.

DC-MHS

OCP Modular Architecture

DC-MHS design with 2x OCP 3.0 slots keeps infrastructure serviceable and upgradable.

Management

Centralized EDCC Control

Redfish-based management via the EnGenius Data Center Controller.

Memory

8TB DDR5 Capacity

Up to 32x DDR5 ECC RDIMM running at 6400 MT/s across both processors.

Expansion

Gen5 Acceleration

2x PCIe Gen5 expansion slots host GPUs and SmartNICs in 1U.

Scalability

CXL 2.0 Ready

CXL 2.0 support enables future-ready memory and device expansion.




Reliability

Titanium Redundant Power

M-CRPS 2000W at 96% Titanium efficiency with hot-swap redundancy.

EnGenius Data Center Controller Centralized Management

The EnGenius Data Center Controller (EDCC) is the cornerstone of simplified, efficient management for your EnGenius data center servers. This powerful, license-free platform provides comprehensive out-of-band management capabilities, empowering IT teams with unparalleled control and visibility over their entire server fleet from a single interface.



Simplified Firmware Updates

Push unified firmware updates to multiple servers simultaneously, ensuring consistency and reducing maintenance overhead.

Out-of-Band Control

Manage servers even if the operating system is unresponsive or powered off, ensuring continuous uptime and remote troubleshooting.

Unified Device Management

Centralized control over all EnGenius servers, eliminating the need for individual server access.

Visual POD View

Gain a physical-to-logical view of server groupings with intuitive POD visualization, enabling more efficient resource mapping, configuration, and infrastructure monitoring.

Remote Diagnostics & Troubleshooting

Gain real-time insights into server health, performance metrics, and system logs, enabling proactive issue identification and rapid resolution from anywhere.

Scalable Deployment

Designed to manage a growing number of servers, providing seamless scalability as your data center expands.

Technical Specifications



EnGenius AI Server	
Model Name	1U Data Center Server
Model Number	S11
Form Factor	1U Rackmount
Processor	Intel Xeon 6 (6500/6700 Series) P Core: Up to 144 E Core: Up to 86 Dual processor, TDP up to 350W
Socket Type	2 x LGA4710
PCH Chipset	No
Memory	Slot Count: 32 DIMM slots (16 DIMMs per CPU) DDR5 ECC RDIMM 6400MT/s 1DPC 5200MT/s 2DPC Capacity: 8TB with 256 GB DDR5
Drive Bays	Up to 12x 2.5"NVMe PCIe Gen5 Hot-Swap drive bays Intel VROC Key Header
System Cooling	Air Cooling 8 x Smart FAN (40 x 40 x 56 mm)
Expansion Slot	Rear: 1x PCIe Gen5 x8 HHHL 1x PCIe Gen5 x16 FHHL 2x OCP3.0 x8 SFF
I/O Port	Front: 2x USB3.0 Type A Rear: 1x USB3.0 Type A for BMC 1x Mini Display for BMC 1x USB3.0 Console for BMC 1x MGNT GE for BMC
Power Supply	M-CRPS 2000W/2200W, per PSU model 80 Plus Titanium Level (96%) 2x Hot Swap Redundant AC Input 110V - 240V
Security	Trusted Platform Module(TPM) 2.0 Platform Firmware Resilience (PFR) 4.0 Intrusion Detection (Open Chassis Cover)
Chassis	Dimension (W x D x H):438 x 790 x 44 (mm) Weight: around 18KG
Environment	Operating Temperature: 10°C to 35°C Storage Temperature: -20°C ~60°C Relative Humidity: 10%~90% (Non-Condensing)

Technical Specifications

System Management	IPMI 2.0 Management Redfish Management HTTPS Web Management IPv4/ IPv6 Address Dashboard Hardware Sensor Monitor KVM console Serial over LAN Virtual Media Firmware Upgarde(BMC/BIOS) Event Log & Alert (SMTP/ SNMP/Syslog) LDAP/ Windows AD/ Radius User Account Management System Firewall (IP Access Control) Hardware Root of trust (RoT) Backup & Restore Configuration Protocol support: SNMP, SMTP, DHCP, NTP, DNS, Dynamic DNS Intel Platform Feature: Platform Firmware Resilience (PFR), Autonomous Crash Dump (ACD),
Central Management	EnGenius Data Center Controller

Hardware Overview

S11 (1U Data Center Server)



DC-SCM:
1 x USB Type A (Console)
1 x USB Type A
1 x RJ45 GbE MGMT Port
1 x Mini Display Port

Slot 01~02:
Slot01: PCIe 5.0 x8, HHHL
Slot02: PCIe 5.0x16, FHHL



Features and specifications subject to change without notice. Trademarks and registered trademarks are the property of their respective owners. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses, and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. Operation of this equipment in a residential area is likely to cause harmful interference in which case the user will be required to correct the interference at his/her own expense. Prior to installing any surveillance equipment, it is your responsibility to ensure the installation is in compliance with local, state and federal video and audio surveillance and privacy laws.

